FIELD REPORT



"THE MU-COLLECT QUICKLY IMPRESSED ME IN PRACTICAL USE - IT PERFORMS TWO WORK STEPS IN ONE AND PROVIDES GOOD **SURFACE OUTPUT TO BOOT"**

Jürgen Kutscher, Garten- und Landschaftsbau Kutscher, Salzkotten-Thüle

lect during a demonstration on a My requirements for the mulcher time later, I was able to test the machine extensively at my own ball turf at SC Paderborn.

whether the MU-Collect collects **be collected!** the material cleanly during scarifying was unfounded: Even under adverse conditions, the im-

I became aware of the MU-Col-plement delivers a great result.

neighbouring golf course. A short were very stringent as it is mainly

I need the surface to be perfec- That's what impressed me! In year. My initial scepticism about tly scarified and all material to addition, we can use the MU-Col-

> These requirements have been fully met. I have a high surfa-

ce output and can do two work

first-class work result!

lect all year round. When I'm not working on the sports grounds, I use the implement for classic mulching work on larger com-

mercial areas - even when there is steps at the same time with only a lot of growth or for collecting leaves in autumn. This means that used on the well-manicured foot- So I save time and money with a I achieve a high utilisation rate with the mulcher throughout the

MÜTHING MULCHERS



STAY ONE STEP AHEAD WITH CERTIFIED SAFETY!

- Europe's agricultural machinery manufacturers have to manufacture their machines in accordance with CE machinery directives.
- Applying the CE marking is a self-declaration of compliance with the CE machinery directives.
- One of these CE machinery directives is entitled: "Thrown-object test and acceptance criteria for flail mulchers as per ISO/WD 17101-2"
- We went one step further and commissioned an independent, accredited institute to assess and certify our compliance with this machinery directive.



Your contact:



Maximum safety and worry-free operation

with observation of the safety clearances of 8 metres towards the front and rear and 2 metres towards the right and left.



Müthing GmbH & Co. KG Soest

Am Silberg 23 D-59494 Soest

Tel. +49 (0) 2921 96510 Fax + 49 (0) 2921 73080 soest@muething.com www.muething.com











A MULCHER FOR ALL SEASONS

PERFECTLY MAINTAINED SURFACES -**FLEXIBLE AND TIME-SAVING**

MU-COLLECT VARIO MU-COLLECT HYDRO VARIO

THE ALL-ROUNDER

ONE MULCHER. **MANY POSSIBILITIES**

Mulch or collect -Decide when you get there

Everything is possible with the MU-Collect Vario: An exact mulching result, a perfectly scarified surface and cleanly collected mulch.

- Thanks to the easily replaceable scarifying blades, the grass is scarified a few millimetres deep to remove weeds and moss.
- The soil is aerated so that optimal irrigation is ensured.
- The available working widths of 1.4 and 1.6 m enable efficient mulching or scarifying even on larger areas such as sports grounds, golf courses or parks.
- A feeder auger brings the mulch material together to ensure reliable operation even under high throughput levels. The special delivery chute prevents blockages due to material backup or full containers.



fying blades with corresponding spacer bushings are installed instead of the shackle flails. The loose suspension allows the blades to avoid foreign bodies such as stones. With blades rotating at 45 m/s, the matted layer in the root crown area is actively cut and aerated; the result is a long-lasting improvement in the soil structure.



The MU-Vario® system equipped as standard ensures perfect shredding and increases the loading capacity.




Changing the operating mode is very The rotating blades specifically cut and aerate the matted layer in the root crown simple. To do so, the respective scariarea (top of picture: before scarifying, bottom of picture: after scarifying).

Driving power: 20 - 40 HP Working width: 1.4 - 1.6 m Hydraulic output: 30 to 70 l/min

- Vehicle-specific discharge at centre or right
- Optimal accessibility for fast conversion from collecting to mulching function
- Adjustable Müthing Vario cutting bar available
- The short-cut angle ensures a clean work result even with low crop height (optional)
- · Infinitely variable height adjustment of working width





The discharge plate is used to switch from the collecting to the mulching function.



V-belt for reliable power transmission and overload protection.


Technical information

MU-Collect Vario MU-Collect Vario Hydro	140	160
Working width (cm)	140	160
External width (cm)	162	182
Max. tractor HP 2200 rpm	40	40
Weight (kg)	223	244
Number of carbide M-shackle flails	24	28
Oil volume, l/min	35-70	45-70

VERSATILE IN USE, A MULTI-TALENT IN LANDSCAPING



Playing fields Public areas such as playing fields require particularly thorough care. Material can either be collected or left on the surface. A discharge plate allows a quick change between collecting the mulch and depositing it on the lawn.





Sports ground Exact cutting lengths of 2.7 cm are no problem thanks to the specially developed short-cut flap and the adjustable cutting bar. Optionally, the material can be collected immediately.

See the MU-Collect Vario in action here.

Just scan the QR code to get started.



Golf course Whether it be on the tee, the fairway or the apron zone, the scarifying blades rotating at 45 m/s specifically cut up the matted layer down to the root crown area and thus bring sufficient air to the roots. The direct collection of the scarified material in one operation protects the surface.

Suitable adaptation options for many carrier vehicles





The MU-Collect in year-round use



Scarifying in spring





ARRANGE A DEMONSTRATION APPOINTMENT!



Telephone +49 (0)2921 3704968 info@muething.com



Cat. 0 coupling triangle

Cat.1 coupling triangle

Mounting console for support arms